

Best Septic Tank Value in the Industry



No Assembly Required

Durable:

- Rotationally molded rugged, one-piece tank with no seams to leak.
- Superior structural design.

Convenient:

- No special backfill or water filling required during installation.
- May be pumped dry during pump-outs.
- May be installed with 6" to 36" of cover.
- Suitable for use as a septic tank or pump tank and may also be used for non-potable water.
- Access openings and lids accept NexGen D2 manhole extension, double wall corrugated pipe, and ribbed PVC pipe.
- Tanks are available with PVC tees and gaskets supplied.
- Available in the sizes you need, 750, 1000, 1250 and 1500 gallon capacity.

Economical:

- No need for installation crews to sit idle waiting for tank delivery.
- Can be moved into position without the use of heavy equipment.



For installation details, please visit www.snydernet.com

NexGen D2™

LOW PROFILE SEPTIC TANKS

Capacity (Gallons)	Length (Inches)	Width (Inches)	Height (Inches)	Manhole DIA (Inches)	Single Compartment P/N	Double Compartment P/N
750	92	60	51	2 - 20" (63672)	43495	43499
1000	127	60	51	2 - 20" (63672)	42405	43517
1250	157	60	51	2 - 20" (63672)	43519	43503
1500	157	69	51	2 - 20" (63672)	43518	43504

LOW PROFILE CISTERN TANKS

Capacity (Gallons)	Length (Inches)	Width (Inches)	Height (Inches)	Manhole DIA (Inches)	Part No.
1175	127	60	51	2 - 20" (63672)	44405
1725	157	69	51	2 - 20" (63672)	44407



LOW PROFILE ACCESSORIES

Description	Part No.
20" NexGen D2 Lid with gasket	63672
Gasketed Manhole extension (6"H x 20"D)*	63832
Gasketed Manhole extension (15"H x 20"D)*	63833
Gasketed Manhole extension (24"H x 20"D)*	63834
Gasketed Lid riser, offset (23"H x 12"D)*	63831

